

EVERPURE® CARTRIDGE REFERENCE GUIDE

PRODUCT	CARTRIDGE PART NO	RATED CAPACITY GALS / LITRES	MICRON RATING	APPLICATIONS								BENEFITS								NSF			
				COFFEE	ESPRESSO	DRINKING WATER	ICED TEA	FOUNTAIN	ICE	BOILERLESS STEAM	BOILER STEAM	CHLORINE, TASTE & ODOR	SCALE INHIBITION	PARTICULATE	TURBIDITY REDUCTION	LEAD REDUCTION	CYST REDUCTION**	CHLORAMINES	BACTERIOSTATIC** CONTROL		BACTERIA REDUCTION		
2CB5	EV9617-05	3,000 / 11,355	5.0	•		•		•					•		•								42
2CB5-K	EV9617-06	3,000 / 11,355	5.0	•		•							•	•	•						•		42
2CB5-S	EV9617-22	3,000 / 11,355	5.0	•		•	•						•	•	•								42
2CB-GW	EV9618-36	3,000 / 11,355	10	•									•	•	•								N/A
2FC	EV9691-56	6,000 / 22,710	0.5			•							•		•				•		•		42, 53
2FC-S	EV9691-76	6,000 / 22,710	0.5	•		•	•						•	•	•				•		•		42, 53
2FC5	EV9691-66	6,000 / 22,710	5.0			•		•					•								•		42
2FC5-S	EV9691-86	6,000 / 22,710	5.0	•						•			•	•							•		42
2H-L	EV9634-26	750 / 2,839	0.5			•							•	•	•			•	•				42, 53
2K-Plus	EV9612-66	1,500 / 5,678	0.5			•							•	•	•				•		•		42
4C ²	EV9605-50	3,900/14,763	0.5			•		•					•		•				•		•		42
4CB5	EV9617-16	6,000 / 22,710	5.0			•		•		•	•		•										42
4CB5-K	EV9617-36	6,000 / 22,710	5.0	•		•							•	•	•						•		42
4CB5-S	EV9617-26	6,000 / 22,710	5.0	•		•				•			•	•	•								42
4FC	EV9692-21	15,000 / 56,781	0.5			•		•					•		•				•		•		42, 53
4FC-S	EV9692-31	15,000 / 56,781	0.5	•						•			•	•	•				•		•		42, 53
4FC5	EV9693-21	15,000 / 56,781	5.0			•		•					•		•						•		42
4FC5-S	EV9693-31	15,000 / 56,781	5.0	•						•			•	•	•						•		42
4FC-L	EV9693-10	4,900 / 18,548	0.5			•		•					•		•	•	•	•	•	•	•	•	42, 53
4FC-LS	EV9693-16	4,900 / 18,548	0.5	•		•				•			•	•	•	•	•	•	•	•	•	•	42, 53
4H ²	EV9605-70	3,900/14,763	0.5	•		•							•	•	•				•		•		42
4H-L	EV9635-26	1,000 / 3,785	0.5			•							•	•	•			•	•				42, 53
4K-Plus	EV9612-76	3,000 / 11,356	0.5			•							•	•	•				•		•		42
4SI	EV9606-51	15,000*** / 56,781***	0.5							•			•	•					•				42, 53
7CB5	EV9618-11	10,000 / 37,850	5.0					•		•	•		•										42
7BC5-K	EV9617-76	10,000 / 37,850	5.0	•																			42
7CB5-S	EV9618-21	10,000 / 37,850	5.0	•						•			•	•	•								42
7CLM+	EV9771-00	7,500 / 28,391	5.0			•		•					•		•				•	•			42, 53

*Based on 10 grains of hardness (with Claris, a bypass setting of 4).
 **Harmful cyst and microbial reduction by mechanical means. For further information concerning FIFRA registration, see product specification sheets.
 ***Grains reduction.
 Note: See individual system specification sheets for performance claims and FIFRA registration information.

EVERPURE® CARTRIDGE REFERENCE GUIDE

PRODUCT	CARTRIDGE PART NO	RATED CAPACITY GALS / LITRES	MICRON RATING	APPLICATIONS								BENEFITS								NSF	
				COFFEE	ESPRESSO	DRINKING WATER	ICED TEA	FOUNTAIN	ICE	BOILERLESS STEAM	BOILER STEAM	CHLORINE, TASTE & ODOR	SCALE INHIBITION	PARTICULATE	TURBIDITY REDUCTION	LEAD REDUCTION	CYST REDUCTION**	CHLORAMINES	BACTERIOSTATIC** CONTROL		BACTERIA REDUCTION
7FC	EV9692-61	25,000 / 94,635	0.5			•		•					•		•						42, 53
7FC-L	EV9693-40	7,400 / 28,012	0.5			•		•													42, 53
7FC-S	EV9692-71	25,000 / 94,635	0.5	•						•			•	•	•				•	•	42, 53
7FC-LS	EV9693-46	7,400 / 28,012	0.5	•		•				•											42, 53
7FC5	EV9693-61	25,000 / 94,635	5.0			•		•					•		•					•	42
7FC5-S	EV9693-71	25,000 / 94,635	5.0	•						•			•	•	•					•	42
7SI	EV9606-01	25,000*** / 94,635***	0.5							•				•	•					•	42, 53
AC ²	EV9605-80	1,500 / 5,678	0.5			•							•		•					•	42
BH ²	EV9612-50	3,000 / 11,355	0.5	•				•					•	•	•					•	42, 53
Claris™ Ultra S	EV4339-80	660* / 2,500	5.0	•	•			•					•	•							42
Claris Ultra M	EV4339-81	1,109* / 4,200	5.0	•	•			•					•	•							42
Claris Ultra L	EV4339-82	2,245* / 8,500	5.0	•	•			•					•	•							42
Claris Ultra XL	EV4339-83	3,196* / 12,100	5.0	•	•			•					•	•							42
Claris Ultra XXL	EV4339-84	5,283* / 20,000	5.0	•	•			•					•	•	•						42
Claris Prime	EV4339-86	557 / 2,110 1,255 / 4,750	5.0	•	•			•		•	•										42
ESO ⁶	EV9607-10	4,100*** / 15,520***	N/A	•	•			•													N/A
ESO ⁷	EV9607-25	5,300*** / 20,063***	N/A	•	•			•													N/A
i2000 ²	EV9612-22	9,000 / 34,065	0.5							•			•	•	•					•	42, 53
i4000 ²	EV9612-32	12,000 / 45,420	0.5							•			•	•	•					•	42, 53
MC ²	EV9612-56	9,000 / 34,069	0.5			•		•					•		•					•	42, 53
MH ²	EV9613-21	9,000 / 34,069	0.5	•				•					•	•	•					•	42, 53
MicroGuard™ Pro 2	EV9637-01	2,200 / 8,328	0.15			•							•		•					•	N/A
MicroGuard Pro 4	EV9637-02	3,600 / 13,627	0.15			•							•		•					•	N/A
OCS ²	EV9618-02	1,500 / 5,678	0.5	•				•					•	•	•					•	42, 53
OW200L	EV9619-06	480 / 1,817	0.5			•							•	•	•						42
OW2-Plus	EV9634-06	1,000 / 3,785	0.5			•							•	•	•					•	42
OW4-Plus	EV9635-06	2,000 / 7,571	0.5			•							•	•	•					•	42
SEN	EV9692-65	50,000 / 189,270	0.5			•		•					•		•					•	42, 53
XC ²	EV9613-10	12,000 / 45,425	0.5			•		•					•		•					•	42, 53
XCLM ⁺	EV9761-00	9,300 / 35,204	5.0			•		•					•		•					•	42, 53

*Based on 10 grains of hardness (with Claris, a bypass setting of 4).

**Harmful cyst and microbial reduction by mechanical means. For further information concerning FIFRA registration, see product specification sheets.

***Estimated. Actual capacity may vary depending on volume of particulate in incoming water.

Note: See individual system specification sheets for performance claims and FIFRA registration information.

EVERPURE® SYSTEM REFERENCE GUIDE

PRODUCT	SYSTEM PART NO	FLOW RATE GPM / LPM	RATED CAPACITY GALS / LITRES	MICRON RATING	APPLICATIONS												BENEFITS								NSF
					COFFEE	ESPRESSO	FOUNTAIN	DRINKING WATER	ICED TEA	FROZEN CARBONATED BEVERAGE (FCB)	ICE	BOILERLESS STEAM	BOILER STEAM	WAREWASHING	CHLORINE, TASTE & ODOR	CHLORAMINES	SCALE INHIBITION	SCALE REDUCTION	PARTICULATE	TOTAL DISSOLVED SOLIDS (TDS)	MINERAL BOOST	MINERAL BLENDING	CYST REDUCTION***	BACTERIOSTATIC***	
QL2-OCS ²	EV9275-60	0.50 / 1.89	1,500 / 5,678	0.5	•												•	•	•				•	•	42, 53
QL3-BH ²	EV9272-00	0.50 / 1.89	3,000 / 11,636	0.5	•												•	•	•				•	•	42, 53
QC7I Single-MH ^{2*}	*	1.67 / 6.32	9,000 / 34,907	0.5	•												•	•	•				•	•	42, 53
QC7I Twin-MH ²	*	3.34 / 12.64	18,000 / 69,813	0.5	•												•	•	•				•	•	42, 53
QC7I Single-ESO ⁶	*	0.50 / 1.89	409** / 1,586	5.0		•											•	•	•						-
QC7I Single-ESO ⁷	*	0.50 / 1.89	531** / 2,059	5.0		•											•	•	•						-
QC7I Twin-ESO ⁷	*	1.00 / 3.79	1,062** / 4,119	5.0		•											•	•	•						-
QC7I Triple-ESO ⁷	*	1.50 / 5.68	1,593** / 6,178	5.0		•											•	•	•						-
QC7I Single-MC ²	EV9275-01	1.67 / 6.32	9,000 / 34,907	0.5			•	•	•								•	•	•				•	•	42, 53
QC7I Twin-MC ²	EV9275-02	3.34 / 12.64	18,000 / 69,813	0.5			•	•	•								•	•	•				•	•	42, 53
QC7I Triple-MC ²	EV9275-03	5.00 / 18.93	27,000 / 104,720	0.5			•	•	•								•	•	•				•	•	42, 53
QC7I Quad-MC ²	*	6.70 / 25.36	36,000 / 139,626	0.5			•	•	•								•	•	•				•	•	42, 53
QC7I Single-7CLM ⁺	EV9771-11	1.67 / 6.32	7,500 / 28,391	5.0			•	•	•								•	•	•						42
QC7I Twin-7CLM ⁺	EV9771-12	3.34 / 12.64	15,000 / 56,781	5.0			•	•	•								•	•	•						42
QC7I Triple-7CLM ⁺	EV9771-13	5.01 / 18.96	22,500 / 85,172	5.0			•	•	•								•	•	•						42
QC7I Quad-7CLM ⁺	EV9771-14	6.68 / 25.29	30,000 / 113,562	5.0			•	•	•								•	•	•						42
QC7I Single-XCLM ⁺	EV9761-11	2.00 / 7.57	9,300 / 35,204	5.0			•	•	•								•	•	•						42
QC7I Twin-XCLM ⁺	EV9761-12	4.00 / 15.14	18,600 / 70,409	5.0			•	•	•								•	•	•						42
QC7I Triple-XCLM ⁺	EV9761-13	6.00 / 22.71	27,900 / 105,613	5.0			•	•	•								•	•	•						42
QC7I Quad-XCLM ⁺	EV9761-14	8.00 / 30.28	37,200 / 140,817	5.0			•	•	•								•	•	•						42
Coldrink® 1-MC ²	EV9328-01	1.67 / 6.32	9,000 / 34,907	0.5			•	•	•								•	•	•				•	•	42, 53
Coldrink 2-MC ²	EV9328-02	3.34 / 12.64	18,000 / 69,813	0.5			•	•	•								•	•	•				•	•	42, 53
Coldrink 3-MC ²	EV9328-03	5.00 / 18.93	27,000 / 104,720	0.5			•	•	•								•	•	•				•	•	42, 53
Coldrink 4-4FC	EV9328-44	10.00 / 37.85	60,000 / 232,710	0.5			•	•	•								•	•	•				•	•	42, 53
Coldrink 3-7FC	EV9328-73	7.50 / 28.39	75,000 / 290,888	0.5			•	•	•								•	•	•				•	•	42, 53
Coldrink 4-7FC	EV9328-74	10.00 / 37.85	100,000 / 387,850	0.5			•	•	•								•	•	•				•	•	42, 53
Coldrink 1-7CLM ⁺	EV9771-21	1.67 / 6.32	7,500 / 28,391	5.0			•	•	•								•	•	•						42
Coldrink 2-7CLM ⁺	EV9771-22	3.34 / 12.64	15,000 / 56,781	5.0			•	•	•								•	•	•						42
Coldrink 3-7CLM ⁺	EV9771-23	5.01 / 18.96	22,500 / 85,172	5.0			•	•	•								•	•	•						42
Coldrink 4-7CLM ⁺	EV9771-24	6.68 / 25.29	30,000 / 113,562	5.0			•	•	•								•	•	•						42
Coldrink 1-XCLM ⁺	EV9761-21	2.00 / 7.57	9,300 / 35,204	5.0			•	•	•								•	•	•						42
Coldrink 2-XCLM ⁺	EV9761-22	4.00 / 15.14	18,600 / 70,409	5.0			•	•	•								•	•	•						42
Coldrink 3-XCLM ⁺	EV9761-23	6.00 / 22.71	27,900 / 105,613	5.0			•	•	•								•	•	•						42
Coldrink 4-XCLM ⁺	EV9761-24	8.00 / 30.28	37,200 / 140,817	5.0			•	•	•								•	•	•						42
Insuric® Single PF-i2000 ²	EV9324-21	1.67 / 6.32	9,000 / 34,907	0.5						•							•	•	•				•	•	42, 53
Insurice Single-i2000 ²	EV9324-01	1.67 / 6.32	9,000 / 34,907	0.5						•							•	•	•				•	•	42, 53
Insurice Twin PF-i2000 ²	EV9324-22	3.34 / 12.64	18,000 / 69,813	0.5						•							•	•	•				•	•	42, 53
Insurice Twin-i2000 ²	EV9324-02	3.34 / 12.64	18,000 / 69,813	0.5						•							•	•	•				•	•	42, 53

*Head and filter cartridge sold separately.

**Based on 10 grains of hardness (with Claris, a bypass setting of 4).

***Harmful cyst and microbial reduction by mechanical means. For further information concerning FIFRA registration, see product specification sheets.

EVERPURE® SYSTEM REFERENCE GUIDE

PRODUCT	SYSTEM PART NO	FLOW RATE GPM / LPM	RATED CAPACITY GALS / LITRES	MICRON RATING	APPLICATIONS											BENEFITS						NSF		
					COFFEE	ESPRESSO	FOUNTAIN	DRINKING WATER	ICED TEA	FROZEN CARBONATED BEVERAGE (FCB)	ICE	BOILERLESS STEAM	BOILER STEAM	WAREWASHING	CHLORINE, TASTE & ODOR	CHLORAMINES	SCALE INHIBITION	SCALE REDUCTION	PARTICULATE	TOTAL DISSOLVED SOLIDS (TDS)	MINERAL BOOST		MINERAL BLENDING	CYST REDUCTION***
Endurance® High Flow Twin	EV9437-30	7.50 / 28.39	100,000 / 387,850	0.5	•	•	•	•													•	•	•	42, 53
Endurance High Flow Triple	EV9437-31	11.25 / 42.59	150,000 / 581,775	0.5	•	•	•														•	•	•	42, 53
Endurance High Flow Quad	EV9437-32	15.00 / 56.78	200,000 / 775,700	0.5	•	•	•														•	•	•	42, 53
Endurance TKO MicroFilter	EV9437-50	15.00 / 56.78	NA	0.65																	•			–
2SR-BW Endurance Feeder Kit	EV9798-70	NA	NA	NA	•					•		•									•			–
2SR-BW QL2 Feeder Kit	EV9798-75	NA	NA	NA	•					•		•									•			–
Endurance SC Twin	EV9437-40	7.50 / 28.39	100,000 / 378,541	0.5	•	•	•														•	•	•	42, 53
Endurance SC Triple	EV9437-41	11.25 / 42.59	150,000 / 567,812	0.5	•	•	•														•	•	•	42, 53
Endurance SC Quad	EV9437-42	15.00 / 56.78	200,000 / 757,082	0.5	•	•	•														•	•	•	42, 53
CB20-124E	EV9100-51	5.00 / 18.93	15,000 / 58,178	5.0			•	•	•												•	•		–
CB20-302E	EV9100-32	5.00 / 18.93	20,000 / 77,570	5.0			•	•	•												•	•		–
CB20-312E	EV9100-37	5.00 / 18.93	85,000 / 329,673	0.5			•	•	•												•	•		42, 53
LVRO-75HE	EV9975-00	NA	14.66 / 55.49	NA																	•	•		58
LVRO-75HE+F	EV9975-10	NA	14.66 / 55.49	NA																	•	•		58
Conserv® LT-S	EV9975-20	NA	50.51/191.20	NA																				–
Conserv 75S	EV9976-00	NA	50.51 / 191.20	NA																	•	•	•	58
Conserv 75E	EV9977-00	NA	50.51 / 191.20	NA	•	•															•	•	•	58
MRS-20	EV9797-91	NA	Up to 20 gpd	NA																	•	•		–
MRS-100	EV9970-07	NA	Up to 100 gpd (more with blend)	NA	•	•															•	•		–
MRS-100BL	EV9970-73	NA	Up to 100 gpd (more with blend)	NA	•	•															•	•		–
MRS-100CC-BL	EV9973-63	NA	Up to 100 gpd	NA	•	•															•	•	•	–
MRS-225	EV9970-08	NA	Up to 225 gpd	NA	•	•															•	•		–
MRS-225BL	EV9970-76	NA	Up to 225 gpd (more with blend)	NA	•	•															•	•		–
MRS-225CC-BL	EV9970-19	NA	Up to 225 gpd (more with blend)	NA	•	•															•	•	•	–
MRS-350	EV9970-17	NA	Up to 350 gpd	NA	•	•															•	•		–
MRS-350BL	EV9970-20	NA	Up to 350 gpd (more with blend)	NA	•	•															•	•		–
MRS-350CC-BL	EV9973-65	NA	Up to 350 gpd (more with blend)	NA	•	•															•	•	•	–
MRS-600HE	EV9970-38	NA	Up to 760 gpd (more with blend)	NA	•	•															•	•		58
MRS-600HE-II	EV9970-54	NA	Up to 507 gpd (more with blend)	NA	•	•															•	•		58
NEW Conserv HE-3	EV9977-50	NA	Up to 1200 gpd (more with blend)	0.5	•	•															•	•	•	42, 53, 58
Kleensteam® CT	EV9797-50	1.67 / 6.32	6,000 / 23,271	5.0																	•	•		–
Kleensteam II Single	EV9797-21	2.50 / 9.46	10,000 / 38,785	5.0																	•	•		–
Kleensteam II Twin	EV9797-22	5.00 / 18.93	20,000 / 77,570	5.0																	•	•		–
SR-X Scale Inhibitor System	EV9797-20	6.00 / 22.71	NA	0.5	•																•	•		–
Kleenware® HTS-11	EV9799-11	15.00 / 56.78	NA	NA																	•	•		–

*Head and filter cartridge sold separately.

**Based on 10 grains of hardness (with Claris, a bypass setting of 4).

***Harmful cyst and microbial reduction by mechanical means. For further information concerning FIFRA registration, see product specification sheets.