

EVERPURE[®] CARTRIDGE REFERENCE GUIDE

PRODUCT	CARTRIDGE PART NO	RATED CAPACITY GALS / LITRES	MICRON RATING	APPLICATIONS								BENEFITS								NSF		
				COFFEE	ESPRESSO	DRINKING WATER	ICED TEA	FOUNTAIN	ICE	BOILERLESS STEAM	BOILER STEAM	CHLORINE, TASTE & ODOR	SCALE INHIBITION	PARTICULATE	TURBIDITY REDUCTION	LEAD REDUCTION	CYST REDUCTION**	CHLORAMINES	BACTERIOSTATIC** CONTROL		BACTERIA REDUCTION	
2CB5	EV9617-05	3,000 / 11,355	5.0	•		•		•					•		•							42
2CB5-K	EV9617-06	3,000 / 11,355	5.0	•		•							•	•	•					•		42
2CB5-S	EV9617-22	3,000 / 11,355	5.0	•		•	•						•	•	•							42
2CB-GW	EV9618-36	3,000 / 11,355	10	•									•	•	•							N/A
2FC	EV9691-56	6,000 / 22,710	0.5			•							•		•	•			•	•		42, 53
2FC-S	EV9691-76	6,000 / 22,710	0.5	•		•	•						•	•	•	•			•	•		42, 53
2FC5	EV9691-66	6,000 / 22,710	5.0			•		•					•						•			42
2FC5-S	EV9691-86	6,000 / 22,710	5.0	•					•				•	•					•			42
2H-L	EV9634-26	750 / 2,839	0.5			•							•	•	•		•	•				42, 53
2K-Plus	EV9612-66	1,500 / 5,678	0.5			•							•	•	•			•	•			42
4C ²	EV9605-50	3,900 / 14,763	0.5			•		•					•		•			•	•			42
4CB5	EV9617-16	6,000 / 22,710	5.0			•		•		•			•		•							42
4CB5-K	EV9617-36	6,000 / 22,710	5.0	•		•							•	•	•				•			42
4CB5-S	EV9617-26	6,000 / 22,710	5.0	•		•		•					•	•	•							42
4FC	EV9692-21	15,000 / 56,781	0.5			•		•					•		•			•	•			42, 53
4FC-S	EV9692-31	15,000 / 56,781	0.5	•					•				•	•	•			•	•			42, 53
4FC5	EV9693-21	15,000 / 56,781	5.0			•		•					•		•				•			42
4FC5-S	EV9693-31	15,000 / 56,781	5.0	•					•				•	•	•				•			42
4FC-L	EV9693-10	4,900 / 18,548	0.5			•		•					•		•	•	•					42, 53
4FC-LS	EV9693-16	4,900 / 18,548	0.5	•		•			•				•	•	•	•	•					42, 53
4H ²	EV9605-70	3,900 / 14,763	0.5	•		•							•	•	•			•	•			42
4H-L	EV9635-26	1,000 / 3,785	0.5			•							•	•	•		•	•				42, 53
4K-Plus	EV9612-76	3,000 / 11,356	0.5			•							•	•	•			•	•			42
4SI	EV9606-51	15,000*** / 56,781***	0.5						•				•	•				•				42, 53
7CB5	EV9618-11	10,000 / 37,850	5.0					•		•			•		•							42
7BC5-K	EV9617-76	10,000 / 37,850	5.0	•		•			•				•	•	•							42
7CB5-S	EV9618-21	10,000 / 37,850	5.0	•					•				•	•	•							42
7CLM+	EV9771-00	7,500 / 28,391	5.0			•		•					•		•			•	•			42, 53

*Based on 10 grains of hardness (with Claris, a bypass setting of 4).
 **Harmful cyst and microbial reduction by mechanical means. For further information concerning FIFRA registration, see product specification sheets.
 ***Grains reduction.
 Note: See individual system specification sheets for performance claims and FIFRA registration information.

EVERPURE[®] CARTRIDGE REFERENCE GUIDE

PRODUCT	CARTRIDGE PART NO	RATED CAPACITY GALS / LITRES	MICRON RATING	APPLICATIONS								BENEFITS							NSF
				COFFEE	ESPRESSO	DRINKING WATER	ICED TEA	FOUNTAIN	ICE	BOILERLESS STEAM	BOILER STEAM	CHLORINE, TASTE & ODOR	SCALE INHIBITION	PARTICULATE	TURBIDITY REDUCTION	LEAD REDUCTION	CYST REDUCTION**	CHLORAMINES	
7FC	EV9692-61	25,000 / 94,635	0.5			•	•					•	•		•	•	•	•	42, 53
7FC-L	EV9693-40	7,400 / 28,012	0.5			•	•					•	•	•	•	•	•	•	42, 53
7FC-S	EV9692-71	25,000 / 94,635	0.5	•					•			•	•	•	•	•	•	•	42, 53
7FC-LS	EV9693-46	7,400 / 28,012	0.5	•		•			•			•	•	•	•	•	•	•	42, 53
7FC5	EV9693-61	25,000 / 94,635	5.0			•						•	•				•	•	42
7FC5-S	EV9693-71	25,000 / 94,635	5.0	•					•			•	•	•			•	•	42
7SI	EV9606-01	25,000*** / 94,635***	0.5						•			•	•		•				42, 53
AC ²	EV9605-80	1,500 / 5,678	0.5			•						•	•		•		•	•	42
BH ²	EV9612-50	3,000 / 11,355	0.5	•			•					•	•	•	•		•	•	42, 53
Claris™ Ultra S	EV4339-80	660* / 2,500	5.0	•	•		•					•	•	•					42
Claris Ultra M	EV4339-81	1,109* / 4,200	5.0	•	•		•					•	•	•					42
Claris Ultra L	EV4339-82	2,245* / 8,500	5.0	•	•		•					•	•	•					42
Claris Ultra XL	EV4339-83	3,196* / 12,100	5.0	•	•		•					•	•	•					42
Claris Ultra XXL	EV4339-84	5,283* / 20,000	5.0	•	•		•					•	•	•					42
Claris Prime	EV4339-86	557 / 2,110 1,255 / 4,750	5.0	•	•		•		•	•		•	•	•					42
ESO ⁶	EV9607-10	4,100*** / 15,520***	N/A	•	•		•					•	•	•					N/A
ESO ⁷	EV9607-25	5,300*** / 20,063***	N/A	•	•		•					•	•	•					N/A
i2000 ²	EV9612-22	9,000 / 34,065	0.5						•			•	•	•	•		•	•	42, 53
i4000 ²	EV9612-32	12,000 / 45,420	0.5						•			•	•	•	•		•	•	42, 53
MC ²	EV9612-56	9,000 / 34,069	0.5			•	•					•	•		•		•	•	42, 53
MH ²	EV9613-21	9,000 / 34,069	0.5	•			•					•	•	•	•		•	•	42, 53
MicroGuard™ Pro 2	EV9637-01	2,200 / 8,328	0.15			•						•	•		•		•	•	N/A
MicroGuard Pro 4	EV9637-02	3,600 / 13,627	0.15			•						•	•		•		•	•	N/A
OCS ²	EV9618-02	1,500 / 5,678	0.5	•			•					•	•	•	•		•	•	42, 53
OW200L	EV9619-06	480 / 1,817	0.5			•						•	•	•	•		•	•	42, 53
OW2-Plus	EV9634-06	1,000 / 3,785	0.5			•						•	•	•	•		•	•	42, 53
OW4-Plus	EV9635-06	2,000 / 7,571	0.5			•						•	•	•	•		•	•	42, 53
SEN	EV9692-65	50,000 / 189,270	0.5			•						•	•		•		•	•	42, 53
SEN+	EV9692-66	50,000 / 189,270	0.5	•	•				•			•	•	•	•		•	•	42, 53
XC ²	EV9613-10	12,000 / 45,425	0.5			•	•					•	•		•		•	•	42, 53
XCLM ⁺	EV9761-00	9,300 / 35,204	5.0			•	•					•	•		•	•			42, 53

*Based on 10 grains of hardness (with Claris, a bypass setting of 4).

**Harmful cyst and microbial reduction by mechanical means. For further information concerning FIFRA registration, see product specification sheets.

***Estimated. Actual capacity may vary depending on volume of particulate in incoming water.

Note: See individual system specification sheets for performance claims and FIFRA registration information.